









NAN®TECH 600x600mm VITRIFIED TILES



Company Profile

VITRIFIED is a leading manufacturer and exporter of high quality nano polished vitrified tiles. With a wide range of vitrified tiles, designed and produced in state of the art manufacturing unit at Morbi, India, the company is a force to reckon with.

It has been in business of supply of tiles of global quality, and have been successful in India as well as abroad. With a strong management vision and excellent execution, their brand is one of the most respected in the industry all across the globe.























Ivory Plain



Soft Wood

























Agon
















VITRIFIED TILES 600x600mm





Mimoza



Mosco


















Feather



Legno Gris



















VITRIFIED TILES **600x600mm**





Wave



Fiesta



















Gothic



Italiya

















Orizia


























Ebano Wood

















VITRIFIED TILES **600x600mm**





Sienna



Decora












































Dyna



Pietra



















Amazing



Sparkle



TECHNICAL SPECIFICATION

Sr. No	PROPERTY	International Std. ISO 13006/EN 176 Group Bla	OUR VALUE	Method Of Testing
1.	Deviation in Length	± 0.6%	± 0.1%	EN 98
2.	Deviation in Thickness	± 5.0%	± 3.0%	EN 98
3.	Straightness of sides	± 0.5%	± 0.1%	EN 98
4.	Rectangularity	± 0.6%	± 0.2%	EN 98
5.	Surface Flatness	± 0.5%	± 0.2%	EN 98
6.	Water absorption*	< 0.5%	< 0.05%	EN 99
7.	Mohs hardness*	> 6	> 8	EN 101
8.	Flexural Straightness*	> 27 N/mm ²	> 47 N/mm²	EN 100
9.	Abrasion resistance	< 204 mm ²	< 144 mm²	EN 102
10.	Skid Resistance (Friction Coefficient)	> 0.4	> 0.6	ASTM C-1028
11.	Breaking Strength*	1113 N	2830 N	ASTM C-648
12.	Density (g/cc)	> 2	2.4	DIN 51082
13.	Frost Resistance	Frost Proof	Frost Proof	EN 202
14.	Chemical Resistance	No Damage	No Damage	EN 106
15.	Thermal Shock Resistance	No Damage	No Damage	EN 104
16.	Colour Resistance	No Damage	No Damage	DIN 51094
17.	Thermal Expansion	< 9 x 10-6	< 6 x 10-6	EN 103
18.	Stain Resistance	Resistance	Resistance	ISO 10545-14
19.	Moisture Expansion	Nil	Nil	ISO 10545-10
20.	Glossiness	**	Min 65% - 70% reflection	Glossmeter

PACKING DETAIL

Size	Normal Thickness	No. of Tiles/Box	Coverage Area	Wt. of Box
600 x 600 mm	7.00 mm (Approx)	4 pcs.	1.44 Sq. Mtr.	22 Kgs. (Approx)

APPLICATIONS

























Note: Colours shown are as accurate as the limitations of the printing process will allow. Prospective customers are advised to inspect a sample of the tile before ordering. Every effort has been made to ensure the accuracy of the infomation given. However, the company reserves the right to change the specifications without prior notice.

SPECTO CERAMICA

SI Survey No. 45, 8-A National Highway,

Morbi-363642, (Guj.) India.

Email: specto.export@gmail.com

Web: www.skidooceramica.com

+91 99789 66119